

Computer Vision-Based Model for Detecting Turning Lane Features on Florida's Public Roadways from Aerial Images

Richard Boadu Antwi¹, Michael Kimollo², Samuel Takyi¹, Alican Karaer³, Eren Erman Ozguven¹, Thobias Sando², Ren Moses¹, Maxim Dulebenets¹

1. Department of Civil and Environmental Engineering, Florida A&M University–Florida State University College of Engineering; 2. School of Engineering, University of North Florida; 3. Iteris Inc.

INTRODUCTION

- Efficient collection of roadway geometry data is crucial for effective transportation planning, maintenance, and design. Current land-based techniques are labor-intensive, dangerous, time-consuming and costly, prompting the need for more efficient methodologies.
- Hence, it is imperative to develop innovative, rapid, cheaper, and more efficient methodologies to collect roadway geometry data across the extensive roadway networks.





Literature Review

- RCI data includes all elements, such as, roadway geometry, traffic signals, lane counts, turning restrictions, intersections, pavement markings, signage, pavement condition.
- Traditional methods used for collecting roadway characteristics inventory data by DOTs include field inventory, satellite imagery, integrated GIS/GPS mapping, LiDAR, laser scanning, and photo/video logging.

Our Contributions

- Develop a multiclass object detection model based on YOLO to identify and extract features from aerial images,
- Evaluate the performance of the model with ground truth data, and
- Apply the model to aerial images to detect the all features creating an inventory for Florida's Northwest Counties public roadways.


METHODOLOGY



RESULTS


- Based on the findings, this automated 12-class model averagely detect 23% of features with 94% precision at 75% confidence level. At a lower confidence level of 5%, it can detect 73% of features with 96% precision. At 75% confidence level, the average quality of the model's detection is 16% whereas the average quality of the model is 59% at 5% confidence level.
- On average, the 4-class model recorded 42% of detections with 99% precision at 75% confidence level. At a lower 5% confidence level, 80% of detections were observed at 97% precision. The average quality of the 4-class model detections at 75% confidence level is 28% and 68% at 5% confidence level.

Name | Examples of turning lane feature detection from images





CONFIDENCE (%)	PRECISION (%)		RECALL (%)		QUALITY (%)	
	4-class	12-class	4-class	12-class	4-class	12-class
75	99	94	42	23	28	16
5	97	96	80	73	68	59

Leon County Ground Truth and Detected Turning Lanes



Detected Left, Right, and Center Features in Duval County



CONCLUSIONS

- This study investigates the utilization of computer vision tools for roadway geometry extraction focusing on Florida Counties as a proof of concept.
- This innovative approach aims to replace labor-intensive manual inventory processes with computer vision technology, potentially reducing errors associated with manual data entry.
- By leveraging high-resolution imagery, the developed system can accurately identify turning lane markings from images, offering a cost-effective alternative to human inventory development procedures enhancing the quality of highway geometry data by minimizing manual errors.
- The benefits of this automated roadway data extraction approach for transportation agencies are manifold. It facilitates the identification of outdated or obscured markings, enables the comparison of turning lane locations with other geometric features such as crosswalks and school zones, and supports the analysis of accidents occurring in proximity to these locations.
- Findings were validated using ground truth data from Leon County, Florida and model was applied to detect features in Duval County, Florida.